

QUOTE REQUEST FORM

Name:		Email:						
Company Name:			Project Name:					
Address:			City:	St	ate:	Zip:		
Phone:			Fax:					
	OVERALL	NSIONS OF WALK-IN						
WIDTH:			LENGTH:	HEIGHT:				
Choose from: 5'10", 6'3 ¾", 6'9 Choose from			<i>:</i> 5′10", 6′3 ¾", 6′	,	Choose from: 6'6 ½", 7'6 ½",			
The state of the s			8'2 ¾", 8'8 ½", 9'	8'6½", 9'6 ½", 10'5 ½"				
			10′1 ¾", 10′7 ½", 11′1 ¼",			Taller walk-ins are available.		
			4", 12'6 ½", 13'0 ½	Heights shown are with floor,				
			′6″, 13′11 ¾″, 14′5 ½″, 14′11 ¼″,			subtract 4" for less-floor walk-		
	10 ¾", 16′4 ½", 16′10		34", 16'4 ½", 16'1		ins.			
	9 ¾", 18′3 ½", 18′9		4", 18'3 ½", 18'9 ½ '", 28'3 ½",					
	3 ¾", 20'2 ½" Longer	· ·	¾", 20′2 ½" Longer					
dimensions ar			dimensions are available in					
additional 5 ¾		adaitional 5	¾" increments		\		1 11	
	LOCATION OF BOX		OVERALL CIZE		W	L	Н	
□ INDOOR	☐ OUTDOOR W/ RO	_	OVERALL SIZE					
	☐ FLAT ☐ SLOPED ☐		☐ FREEZER					
	w door locations, expose	ed exterior, &	☐ COOLER					
flashed wall (if outdoor):			☐ 3 rd COMPT.					
			\square 4" Thick \square 5" Thick \square 6" Thick					
City/State if located outdoors:								
FINISHES								
Exterior: (Check one)			Interior: (Check one)					
☐ 26ga Embossed Galvalume			☐ 26ga Embossed Galvalume					
\square 26ga Embossed White Galvalume			☐ 26ga Embossed White Galvalume					
☐ 22ga Smooth Stainless Steel			☐ 22ga Smooth Stainless Steel					
☐ .032 Embossed Aluminum			☐ .032 Embossed Aluminum					
\square .032 Embossed White Aluminum			☐ .032 Embossed White Aluminum					
\square .032 Smooth Aluminum			☐ .032 Smooth Aluminum					
\square .032 Smooth White Aluminum			☐ .032 Smooth White Aluminum					
\square 26ga Embossed San-Tan Galvanized			☐ 26ga Embossed San-Tan Galvanized					
\square 26ga Embossed Black Galvalume			☐ 26ga Embossed Black Galvalume					
If Exposed Exterior & Interior Ceiling need to be different finishes:								
Exposed Exterior: Interior Ceiling:								
Custom finishes available upon request								

FLOORS								
Floor Types: (Check one)	Floor Panel Finishes: (Check one)							
☐ Light Usage	☐ 18ga Smooth Stainless Steel							
☐ Heavy Usage (carts, etc.) reinforced w/	☐ 16ga Smooth Stainless Steel							
□ ¾" Plywood	☐ 5-Bar Tread Foamed-in-place							
□ ½" Plywood	☐ 16ga Galvanized Steel (non NSF- to be used under any NSF							
☐ 1" Plywood	approved Overlay)							
□ PVC Pipe	approved everray)							
□ No Floor, PVC Screed								
☐ No Floor, Fixe Screed	Custom finishes available upon request							
ino Floor, Flat Bottom Walls								
RAMPS	ACCESSORIES							
☐ 27"D Interior Ramp	□ 49" LED Light □ Evtra Vanor LED							
☐ 32"D Exterior Ramp	☐ 48" LED Light ☐ Extra Vapor LED							
☐ Custom Size Ramp:								
DOORS								
No. of Doors:	Door Options:							
Width: Height:	☐ 14" x 14" Non-Heated Cooler Viewport							
Choose from: Choose from: Choose from: 65", 69", 77", 84	☐ 14" x 24" Non-Heated Cooler Viewport							
8 24", 26", 30", 34", 65", 69", 77", 84								
36", 42", 48", 60"	☐ 14" x 24" Heated Freezer Viewport							
Application: Cooler Freezer	☐ Strip Curtain							
Width: Height:	☐ Double Swing Strip Doors							
Choose from: Choose from: 65", 69", 77", 84	☐ Tuffy Door (consist of 3 rd hinge & 36"H 5-Bar Tread							
24", 26", 30", 34", 65", 69", 77", 84	Kickplates)							
36", 42", 48", 60"	☐ S/S Sill Plate							
Application: ☐ Cooler ☐ Freezer	☐ Undercut Door, tile thickness:							
Width: Height:								
Choose from: Choose from:	☐ Glass Display Doors							
<mark> </mark> 24", 26", 30", 34",	" Size:							
36", 42", 48", 60"	Quantity: .							
Application: Cooler Freezer	☐ Sliding Doors							
**Tafco standard door includes hydraulic	Size: .							
door closer, (2) polished hinges, latch, Locking	Quantity:							
Hasp, digital therm./switch, PRP, & VXS100	☐ Manual							
(LED)	□ Electric							
Alarm Systems: ☐ WEISS XWA11V								
☐ Dry Contacts	Framed Opening ONLY							
☐ Panic Alarm	Size:							
☐ Both	Quantity:							
	Door Type							

REFRIGERATION □ Air-Cooled □ Water-Cooled									
Compartment 1	Application: Cooler Freezer Compressor: Hermetic Scroll Semi-Hermetic Self-Contained, drop-in Top-Mount (ONLY)	Compartment 2	Application: Cooler Freezer Compressor: Hermetic Scroll Semi-Hermetic Self-Contained, drop-in Top-Mount (ONLY)			Compartment 3	Application: Cooler Freezer Compressor: Hermetic Scroll Semi-Hermetic Self-Contained, drop-in Top-Mount (ONLY)		
	□ 208-230/1/60			EVAPORATOR TYPE					
☐ 208-230/1/60 ☐ 208-230/3/60 ☐ 220-240/1/50 ☐ 220-240/3/50							Standard Center-Mount Reach-in type		
Compartment 1	Product Type: Entering Temp: Final Temp:	Compartment 2	Product Type: Entering Temp: Final Temp:			Compartment 3	Product Type: Entering Temp: Final Temp:		
ACCESSORIES □ Pre-Charged Lines □ 10' □ 20'			CONDENSING UNIT LOCATION/LINE RUN: How many feet is vertical: How many feet is horizontal:						
☐ 30' ☐ FrostLogic Demand Defrost Controller ☐ Freezer ☐ Cooler			ADDITIONAL REFRIGERATION INFO:						
Ada	OPTION litional request not listed:	S			·		NOTES		