



DETAILED QUOTE REQUEST FORM

Name:		Email:	
Company Name:		Project Name:	
Address:		City:	State: Zip:
Phone:		Fax:	

OVERALL DIMENSIONS OF WALK-IN

WIDTH:	LENGTH:	HEIGHT:
Choose from: 5'10", 6'3 3/4", 6'9 1/2", 7'3 1/4", 7'9", 8'2 3/4", 8'8 1/2", 9'2 1/4", 9'8", 10'1 3/4", 10'7 1/2", 11'1 1/4", 11'7", 12'0 3/4", 12'6 1/2", 13'0 1/4", 13'6", 13'11 3/4", 14'5 1/2", 14'11 1/4", 15'5", 15'10 3/4", 16'4 1/2", 16'10 1/4", 17'4", 17'9 3/4", 18'3 1/2", 18'9 1/4", 19'3", 19'8 3/4", 20'2 1/2" Longer dimensions are available in additional 5 3/4" increments	Choose from: 5'10", 6'3 3/4", 6'9 1/2", 7'3 1/4", 7'9", 8'2 3/4", 8'8 1/2", 9'2 1/4", 9'8", 10'1 3/4", 10'7 1/2", 11'1 1/4", 11'7", 12'0 3/4", 12'6 1/2", 13'0 1/4", 13'6", 13'11 3/4", 14'5 1/2", 14'11 1/4", 15'5", 15'10 3/4", 16'4 1/2", 16'10 1/4", 17'4", 17'9 3/4", 18'3 1/2", 18'9 1/4", 19'3", 19'8 3/4", 20'2 1/2" Longer dimensions are available in additional 5 3/4" increments	Choose from: 6'6 1/2", 7'6 1/2", 8'6 1/2", 9'6 1/2", 10'5 1/2" Taller walk-ins are available. Heights shown are with floor, subtract 4" for less-floor walk-ins.
LOCATION OF BOX		W L H
☐ INDOOR ☐ OUTDOOR W/ ROOF ☐ FLAT ☐ SLOPED ☐ FLASHED		OVERALL SIZE
Sketch box. Show door locations, exposed exterior, & flashed wall (if outdoor):		☐ FREEZER ☐ COOLER ☐ 3 rd COMPT.
City/State if located outdoors: _____.		☐ 4" Thick ☐ 5" Thick ☐ 6" Thick

FINISHES

Exterior: (Check one) ☐ 26ga Embossed Galvalume ☐ 26ga Embossed White Galvalume ☐ 22ga Smooth Stainless Steel ☐ .040 Embossed Aluminum ☐ .040 Embossed White Aluminum ☐ .040 Smooth Aluminum ☐ .040 Smooth White Aluminum ☐ 24ga Embossed Sierra-Tan Galvalume ☐ 26ga Embossed Black Galvalume	Interior: (Check one) ☐ 26ga Embossed Galvalume ☐ 26ga Embossed White Galvalume ☐ 22ga Smooth Stainless Steel ☐ .040 Embossed Aluminum ☐ .040 Embossed White Aluminum ☐ .040 Smooth Aluminum ☐ .040 Smooth White Aluminum ☐ 24ga Embossed Sierra-Tan Galvalume ☐ 26ga Embossed Black Galvalume
If Exposed Exterior & Interior Ceiling need to be different finishes:	
Exposed Exterior: _____.	Interior Ceiling: _____.
Custom finishes available upon request	

FLOORS			
Floor Types: <i>(Check one)</i> ☐ Light Usage ☐ Heavy Usage (carts, etc.) reinforced w/... ☐ ¾" Plywood ☐ ½" Plywood ☐ 1" Plywood ☐ PVC Pipe ☐ No Floor, PVC Screed ☐ No Floor, Flat Bottom Walls		Floor Panel Finishes: <i>(Check one)</i> ☐ 18ga Smooth Stainless Steel ☐ 16ga Smooth Stainless Steel ☐ 5-Bar Tread Foamed-in-place ☐ 16ga Galvanized Steel <i>(non NSF- to be used under any NSF approved Overlay)</i>	
		<i>Custom finishes available upon request</i>	
RAMPS		ACCESSORIES	
☐ 27"D Interior Ramp ☐ 32"D Exterior Ramp ☐ Custom Size Ramp: _____.		☐ 48" LED Light ☐ Extra Vapor LED	
DOORS			
No. of Doors: _____.		Door Options: ☐ 14" x 14" Non-Heated Viewport ☐ 14" x 24" Non-Heated Viewport ☐ 14" x 14" Heated Viewport ☐ 14" x 24" Heated Viewport ☐ Strip Curtain ☐ Double Swing Strip Doors ☐ Tuffy Door (consist of 3 rd hinge & 36"H 5-Bar Tread Kickplates) ☐ S/S Sill Plate ☐ Undercut Door, tile thickness: _____	
Door 1	Width: <i>Choose from:</i> 24", 26", 30", 34", 36", 42", 48", 60"	Height: <i>Choose from:</i> 65", 69", 77", 84"	
Application: ☐ Cooler ☐ Freezer			
Door 2	Width: <i>Choose from:</i> 24", 26", 30", 34", 36", 42", 48", 60"	Height: <i>Choose from:</i> 65", 69", 77", 84"	
Application: ☐ Cooler ☐ Freezer			
Door 3	Width: <i>Choose from:</i> 24", 26", 30", 34", 36", 42", 48", 60"	Height: <i>Choose from:</i> 65", 69", 77", 84"	
Application: ☐ Cooler ☐ Freezer			
**Tafco standard door includes hydraulic door closer, (2) polished hinges, latch, Locking Hasp, digital therm./switch, PRP, & VXS100 (LED)			
Alarm Systems: ☐ Digital Therm. ☐ Dry Contacts ☐ Panic Alarm ☐ Both		☐ Glass Display Doors Size: _____. Quantity: _____. ☐ Sliding Doors Size: _____. Quantity: _____. ☐ Manual ☐ Electric ☐ Framed Opening ONLY Size: _____. Quantity: _____. Door Type: _____.	

REFRIGERATION ☐ Air-Cooled ☐ Water-Cooled					
Compartment 1	Application: ☐ Cooler ☐ Freezer Compressor: ☐ Scroll ☐ Self-Contained, drop-in Top-Mount (ONLY)	Compartment 2	Application: ☐ Cooler ☐ Freezer Compressor: ☐ Scroll ☐ Self-Contained, drop-in Top-Mount (ONLY)	Compartment 3	Application: ☐ Cooler ☐ Freezer Compressor: ☐ Scroll ☐ Self-Contained, drop-in Top-Mount (ONLY)
VOLTAGE			EVAPORATOR TYPE		
☐ 208-230/1/60 ☐ 208-230/3/60 ☐ 220-240/1/50 (overseas) ☐ 220-240/3/50 (overseas)			☐ Standard ☐ Center-Mount ☐ Reach-in type		
Compartment 1	Product Type: _____. Entering Temp: _____. Final Temp: _____.	Compartment 2	Product Type: _____. Entering Temp: _____. Final Temp: _____.	Compartment 3	Product Type: _____. Entering Temp: _____. Final Temp: _____.
AMBIENT TEMP			CONDENSING UNIT LOCATION/LINE RUN: _____. How many feet is vertical: _____. How many feet is horizontal: _____.		
☐ 95°F ☐ 100°F ☐ 110°F					
ADDITIONAL REFRIGERATION INFO:					
OPTIONS			NOTES		
Additional request not listed: _____.			_____.		